

**WEST**

Generate Collection

Print

L2: Entry 27 of 42

File: TDBD

Dec 1, 1982

TDB-ACC-NO: NA82123161

DISCLOSURE TITLE: Method of Increasing the Deposition and Etch Rates in Plasma Processes. December 1982.

## PUBLICATION-DATA:

IBM Technical Disclosure Bulletin, December 1982, US

VOLUME NUMBER: 25

ISSUE NUMBER: 7A

PAGE NUMBER: 3161

PUBLICATION-DATE: December 1, 1982 (19821201)

CROSS REFERENCE: 0018-8689-25-7A-3161

## DISCLOSURE TEXT:

1p. A method is described in which magnetic fields locally confined to the substrates are used for RF plasma deposition and RF plasma etching. - From plasma physics, it is known that magnetic fields influence RP plasma. In the cases that have become known so far, the magnetic fields influence the whole plasma, so that the characteristics of the whole plasma volume are dependent upon the magnetic field. - In accordance with the present method the magnetic fields are locally confined to the substrates during RF plasma deposition and RP plasma etching; only the charged plasma particles close to or at the substrate surface are affected; i.e., the surface processes can be controlled independently of reactions in the plasma volume. - The local influence of the magnetic fields leads to a higher deposition rate during plasma etching and to a shorter reaction period. During etching, the etch rate ratios of the various materials are influenced. - In experiments, permanent magnets or electromagnets were arranged below the substrates in such a manner that the magnetic vector acting on the substrate surface is either perpendicular or parallel to the E field of the plasma reactor. During the plasma deposition of SiN(x), using a magnetic field H perpendicular to the E field of the plasma reactor, the deposition rate could be increased by 50 percent. The diffraction index and the etch rate were the same as for a monitor wafer. During the plasma etching of SiN(x), the etch rate at the location of the magnet could be increased by 11 percent, using a magnetic parallel to the E field of the plasma reactor.

SECURITY: Use, copying and distribution of this data is subject to the restrictions in the Agreement For IBM TDB Database and Related Computer Databases. Unpublished - all rights reserved under the Copyright Laws of the United States. Contains confidential commercial information of IBM exempt from FOIA disclosure per 5 U.S.C. 552(b)(4) and protected under the Trade Secrets Act, 18 U.S.C. 1905.

COPYRIGHT STATEMENT: The text of this article is Copyrighted (c) IBM Corporation 1982. All rights reserved.